- Triple Protection
- Made of pure
  DURAPLUSH<sup>®</sup> Foam
- Highest R-Value for
  Energy Efficiency

Leggett & Platt<sup>°</sup> Flooring Products

# Scotchgard<sup>®</sup> Premium

#### **Comfort and Durability**

- DuraPlush<sup>®</sup> foam technology adds superior cushioning and a rich fullness to your carpet
- Condensed, pure urethane foam ensures durability and long-lasting beauty of carpet

## **Triple Protection**

- Block-Out<sup>®</sup> moisture barrier featuring Scotchgard<sup>™</sup> Protector<sup>®</sup> – keeping liquids, spills, and even pet accidents on the surface of the pad for easier and faster cleanup<sup>\*</sup>
- Fresh Dimension<sup>®</sup> antimicrobial inhibits the growth of mold, mildew, and odor-causing bacteria<sup>\*\*</sup>
- Bottom moisture barrier provides additional protection

## **Healthy Home**

- Hypoallergenic
- CRI Green Label Plus-certified for indoor air quality

## **Fundamentally Green**

- 100% recyclable at the end of its useful life
- Contributes toward achieving LEED<sup>®</sup> building credits

Scole

## Peace of Mind

- Insulates home for better energy efficiency
- Reduces noise for a quieter, more enjoyable home
- Life-of-the-Home warranty with additional StairGuard<sup>™</sup> protection
- \* Scotchgard "Protector" applies to the top film only
- \*\* Fresh Dimension<sup>®</sup> blended throughout the product core

## Featuring



FLOORING PRODUCTS

## Scotchgard<sup>®</sup> Premium

## ADVANCED COMFORT SYSTEM<sup>®</sup>

#### **SPECIFICATIONS**

ADVANCED COMPONENTSTEIN	
SPECIFICATION	S SCOTCHGard
Product code:	BZ0370
R-value:	2.22
Thickness:	0.500"
FHA class:	2
Roll size:	6' x 45' (30 yd²)
Cushion color:	White
Triple Protection:	- Block-Out <sup>®</sup> top moisture barrier featuring Scotchgard <sup>®</sup> Protector - Fresh Dimension <sup>®</sup> antimicrobial - Bottom moisture barrier
Certification:	- FHA/HUD/VA (UM72a per ASTM D3574) - CRI Green Label Plus

#### **RECOMMENDED INSTALLATION INSTRUCTIONS**

- 1. Always inspect the floor prior to installation to ensure it's clean and free of debris. Inspect and test for moisture before installing any dual-moisture barrier product. Reference the CRI Carpet Installation Standard.
- 2. When laying cushion over subfloor where old glue is exposed, first sprinkle talcum, baby powder, or baking soda. This will help prevent the cushion from partially sticking to the floor, potentially causing noise.
- 3. If using a pad adhesive, apply a small amount in the corners of the room to help hold the cushion in place during installation. Staples may also be used around the perimeter of the room.
- 4. Use a flexible, moisture-resistant-type tape (no masking or other paper-based tape) at cushion seams and for covering tears, punctures, and staples.

## LIFE-OF-THE-HOME LIMITED WARRANTY

Please visit LPFlooringProducts.com/scotchgard-premium for detailed warranty information.



